



Alcochem Hygiene datasheet

Technical name	: i-trap 250 WP insect control system (Wet Processing)
Attraction grids	: optimises landing behaviour of flying insects for 30% efficiency increase
Area coverage (m ²)	: 250 - 400
Light source (W) (UV-A)	: 4 times 18 watt shatterproof UV-A
Type of UV lamps	: UV Lamps RoHS certified
Electrical supply (V)	: 220 - 240, other voltages upon request
Catch specifications (V)	: by means of long life glue board
Power consumption (W)	: 80
Weight (kg)	: 13
Material	: stainless steel 304 and ABS, non UV-A degradable plastics
Glass protection	: shatterproof tubes included with 95% UV-A transparency
Degree of protection (IP)	: IP 65 (hose proof)
Suitable for	: wet processing areas
Quality standard	: ISO 9001 approval
Guarantee	: 1 year return to base
Int. building norm	: acc. IEC-335-259 int. standard for insect exterminators
Lamp life time (h)	: 9000*
Dimensions (L*D*H)	: 650 x 190 x 400
Safety approval	: yes
CE-approval	: yes
Mounting position	: ceiling mounted, wall mounted or free standing
Cable	: 2 metres cable with European earthed plug
Colour plastics	: broken white
Packaging	: neutral cardboard box included
Manual	: enclosed with the unit in English, French, German and Dutch
Service	: unit can be dismantled without additional tools

(*) after 9000 hours a loss of 30% in efficiency has to be expected and lamps need to be replaced



Authorized dealer :