



Alcochem Hygiene datasheet

Technical name	: i-trap 80 insect control system
Attraction grids	: optimises landing behaviour of flying insects for 30% efficiency increase
Area coverage (m ²)	: 80 - 160
Light source (W) (UV-A)	: 4 times 15 watt shatterproof UV-A
Type of UV lamps	: UV Lamps RoHS certified
Electrical supply (V)	: 220 - 240, other voltages upon request
Catch specifications (V)	: by means of long life glue board
Power consumption (W)	: 70
Weight (kg)	: 6
Material	: coated steel and ABS, non UV-A degradable plastics
Glass protection	: shatterproof tubes included with 95% UV-A transparency
Degree of protection (IP)	: IP 21 (drip proof)
Suitable for	: non humid, dry environments
Quality standard	: ISO 9001 approval
Guarantee	: 1 year return to base
Int. building norm	: acc. EN 60.335-2-59 int. standard for insect exterminators
Lamp life time (h)	: 9000
Dimensions (L*D*H) (mm)	: 500 * 160 * 340
Safety approval	: yes
CE-approval	: yes
Mounting position	: ceiling mounted, wall mounted flag mounting or free standing
Cable	: 2 metres cable with European earthed plug
Colour plastics	: white
Packaging	: full colour box included
Manual	: enclosed with the unit in English
Service	: unit can be dismantled without additional tools

(*) after 9000 hours a significant loss in efficiency has to be expected and lamps need to be replaced



Authorized dealer :