

I-TRAP 120E



The robust 120 m² flag or ceiling mounted insect control unit



I-TRAP 120E

i-trap 120E wall/ceiling mounting system.

With its robust design, the i-trap 120E is recommended for use in professional or industrial environments.

The i-trap 120E can be either (flag) mounted on the wall or ceiling mounted, by utilising the snap on mounting bracket.

The i-trap 120E has an aluminium housing, which makes the unit both light and strong. Once the insects enter the i-trap, they will be effectively controlled by means of a centrally placed glue board. *Easy to service, robust, yet elegant and effective; the i-trap 120E offers it all.*



10 reasons to start using the i-trap 120E unit:

1. The unit can be mounted onto the wall or onto the ceiling.
2. The aluminium housing offers a light but strong body, easy to handle.
3. Glue board placed discreetly behind the lamp, which offers optimised performance.
4. In the heart of the unit are the most powerful UV-A lamps available:
 - Exclusive to ALCOCHEM the Philips Longlife UV-A lamp offers 2 years of effective use. The Philips Longlife lamp is specifically designed to match the fly's vision spectrum with the lamp's output, for optimum attracting power.
5. Effective coverage of areas up to 120 m².
6. Easy to service with direct access to lamps and glue board.
7. Meets ISO 9001 / RoHS & the CE standard. Unit is HACCP compliant.
8. Durable quality components, industrial design.
9. The i-trap 120E is executed with a high frequency ballast.
 - This ballast which offers lower operational costs and makes the use of a starter redundant. The electronic ballast also offers a high frequency light pulse which means the insect cannot distinguish the lamp from natural UV-A light so providing greater attraction.
10. 2 year full guarantee on the mechanical aspects.



Technical specifications

Area coverage	: 120 m ² effective coverage
Light source	: 4 x 15 Watt shatterproof Philips Longlife UV-A lamps T8
Type of UV lamps	: UV-A Lamp RoHS certified
Electrical supply	: 220-240V ~ 50-60 Hz
Catch specifications	: By means of effective glue board
Power consumption	: 68 Watt
Weight	: 6 Kg
Material	: White coated steel casing
Degree of protection	: IP 20
Guarantee	: 2 year return to base
Int. building norm	: acc. IEC 60.335-259 int. standard for insect exterminators
Lamp life time	: 17,500 hrs (*)
Dimensions (H x W x D)	: 365 x 580 x 150 mm (14.3 x 22.8 x 6 inches)
CE-approval	: Yes
Mounting position	: flag, wall or ceiling mounted
Cable & plug	: Included
Packaging	: Strong cardboard box included
Manual	: Enclosed with the unit in English
Service	: Unit can be serviced without special tools



Powered by Philips Longlife UV-A



asimpleswitch.com

(*) After 17,500 hours of use, the Longlife lamp still offers 75% of its initial UV-A output value