



I-TRAP 120E WP

www.insect-trap.net



The robust 120 m² IP 65 flag, wall and ceiling mounted insect control unit



I-TRAP 120E WP

i-trap 120E WP flag, wall or ceiling mounting system.



With its robust design, the i-trap 120E WP is recommended for use in professional or industrial hose-proof environments. The i-trap can be mounted as a flag, wall or ceiling model. Mounting unit is a breeze with the snap-on mounting bracket. The i-trap 120E WP has an aluminium housing, which

makes the unit both light and strong. Once the insects enter the i-trap, they will be effectively controlled by means of a centrally placed glue board.

Easy to service, robust, yet elegant and effective; the i-trap 120E WP offers it all.

Reasons to start using the i-trap 120E WP unit:

- The unit can be mounted onto the wall (*flat mounting or flag mounting*) or onto the ceiling.
- The aluminium housing offers a light but strong body, easy to handle.
- Glue board placed discreetly behind the lamp, which offers optimized performance.
- Philips 15 Watt shatterproof UV lamp.
- Effective coverage of areas up to 120 m².
- Easy to service with direct access to lamps and glue board.
- Meets ISO 9001 / RoHS & the CE standard. Unit is HACCP compliant.
- Durable quality components, industrial design meets IP65 norm.
- The i-trap 100E is executed with a high frequency ballast.
 - *This ballast offers lower operational costs and makes the use of a starter redundant. The electronic ballast also offers a high frequency light pulse which means the insect cannot distinguish the lamp from natural UV-A light so providing greater attraction.*
- 2 year full guarantee on the mechanical aspects.



Technical specifications

Area coverage	: 120 m ² effective coverage
Light source	: 4 x 15 Watt <i>shatterproof</i> Philips UV-A lamps
Type of UV lamps	: UV-A Lamp RoHS certified
Electrical supply	: 110-240 V ~ 50-60 Hz / 220-240 V ~ 50-60 Hz
Catch specifications	: By means of effective glue board
Power consumption	: 65 Watt
Weight	: 6 Kg
Material	: White coated aluminium housing
Degree of protection	: IP X5 (hose proof)
Guarantee	: 2 year return to base
Int. building norm	: acc. IEC 60.335-259 <i>int. standard for insect exterminators</i>
Lamp life time	: 9000 hrs
Dimensions (H x W x D)	: 580 x 365 x 150 mm (22.8 x 14.3 x 6 inches)
CE-approval	: Yes
Mounting position	: Wall, flag or ceiling mounted
Cable & plug	: Included
Packaging	: Strong cardboard box included
Manual	: Enclosed with the unit in English
Service	: Unit can be serviced without special tools